This listing of claims will replace all prior versions, and listings, of claims in the application:

Docket No. P-0913

Listing of Claims:

1-5. (Canceled).

(Currently Amended) A fuel cell system, comprising:

a main fuel cell stack-that an including a plurality of anodes anode and a cathode are

cathodes arranged in a state that in which an electrolyte membrane is interposed therebetween;

a fuel supplying unit device connected with the anode anodes of the main fuel cell stack

by a fuel supplying line-for supplying that supplies hydrogen-including fuel to the anode anodes;

an air supplying unit device connected to the eathode cathodes of the main fuel cell stack

by an air supplying line for supplying that supplies oxygen-including air to the eathode cathodes;

a heating-unit device installed between the fuel supplying line and the air supplying line for heating that heats fuel and air supplied to the main fuel cell stack by using hydrogen

generated at the-anode anodes after reaction as a-heating heat source; and

a sub fuel cell stack-for-using that uses hydrogen generated at the anode anodes during

reaction as fuel.

(Currently Amended) The fuel cell system of claim 6, further comprising:

5

Docket No. P-0913

Amdt. dated December 2, 2009

Reply to Office Action of September 2, 2009

a gas/liquid separator for obtaining that obtains hydrogen generated at the main fuel cell

stack after reaction; and

a recycling line connected between the gas/liquid separator and the fuel supplying-unit

for recollecting device that recollects fuel exhausted from the gas/liquid separator into a fuel

tank.

8. (Currently Amended) The fuel cell system of claim 7, wherein further comprising

an open/close valve-for that selectively-opening opens either a flow channel connecting the

heating unit device and the gas/liquid separator or a flow channel connecting the sub fuel cell

stack and the gas/liquid separator is installed between said two flow channels.

9. (Currently Amended) The fuel cell system of claim 8, further comprising a

controller for maintaining that maintains a temperature of the heating unit as device at a proper

level by controlling a hydrogen amount supplied to the sub fuel cell stack and-for-controlling

that controls an opening degree of an open/close valve in order to supply hydrogen to the sub

fuel cell stack.

10. (Currently Amended) The fuel cell system of claim 9, wherein the controller

controls an opening degree of the open/close valve according to an electric signal applied from a

6

Reply to Office Action of September 2, 2009

temperature sensor installed at the heating unit for detecting device that detects a temperature of the heating unit device.

- 11. (Currently Amended) The fuel cell system of claim 10, wherein the temperature sensor is installed at one of a heat generating part, a fuel pipe, and or an air pipe of the heating unit device.
- 12. (Original) The fuel cell system of claim 9, wherein the controller controls an opening degree of the open/close valve according to an output of the sub fuel cell stack.
- 13. (Currently Amended) The fuel cell system of claim 9, wherein the controller controls an opening degree of the open/close valve according to an electric signal applied from a flow amount sensor installed at the a hydrogen exhausting line-for detecting to detect a hydrogen amount and the temperature sensor installed at the heating-unit-for detecting device to detect a temperature of the heating-unit device.
- (Currently Amended) The fuel cell system of claim 7, wherein the heating-unit device comprises:

Reply to Office Action of September 2, 2009

a housing to which a fuel pipe for passing that passes fuel supplied to the anode anodes

of the main fuel cell stack and an air pipe-for-passing that passes air supplied to the-eathode

cathodes are respectively mounted;

a blast fan installed at the housing for blowing that blows external air to inside of the

housing; and

a combustor at an inside of which a catalyst is mounted and to which oxygen including

air blown by the blast fan and hydrogen exhausted from the gas/liquid separator are respectively

introduced

(Currently Amended) The fuel cell system of claim 6, wherein fuel stored in the

fuel tank is an aqueous solution of NaBH4.

(Original) The fuel cell system of claim 6, wherein the sub fuel cell stack is a

polymer electrolyte membrane fuel cell (PEMFC).

17. (Currently Amended) The fuel cell system of claim 7, wherein the sub fuel cell

stack is constituted in accordance with that comprises a cathode plurality of cathodes to which

oxygen including air is supplied from the air supplying-unit device and an anode a plurality of

anodes to which hydrogen exhausted from the gas/liquid separator is supplied are stacked in a

state-that in which an electrolyte membrane is positioned therebetween.

Serial No. 10/596,917 Amdt. dated <u>December 2, 2009</u> Reply to Office Action of <u>September 2, 2009</u>

Docket No. P-0913

18-27. (Canceled).